LOADING INFORMATION: \*

CENTER STAGE RIGGING: TRIBUTARY LOADING NOT TO

EXCEED 150,000 LBS.

END STAGE RIGGING: TRIBUTARY LOADING NOT TO

EXCEED 100,000 LBS.

DO NOT EXCEED 15,000 LBS. AT PANEL POINTS ON "TA" TRUSSES DO NOT EXCEED 8,000 LBS. AT PANEL POINTS ON "TB" TRUSSES DO NOT EXCEED 2,000 LBS. ON SECONDARY STEEL

FOLLOW SPOT PLATFORM ELEVATION 99'-6" (TYPICAL OF 6 - AT SIDES) OLLOW SPOT PLATFORM ELEVATION 80'-6" TYPICAL OF 4 - AT ENDS) BT-15B TB-2 TA-2 OPEN <del>TA-1</del> <del>18-1</del> BT-15A RING CATWALK ELEVATION VARIES

1 OMAHA ARENA - CATWALK & RIGGING

SECONDARY STEEL ELEVATION 92'-0"

MAIN RIGGING STEEL ELEVATION 92'-0"

\* NOTE: LOADING INFORMATION TO BE VERIFIED BY STRUCTURAL ENGINEER AT CONCLUSION OF CONSTRUCTION.